



SPECIFICATION SHEET Manhattan 69

Manhattan 69 flooring is made of Stone Plastic Composite. **Manhattan 69** floor is designed to exceed. The main component are natural limestone powder polyvinyl chloride and stabilizer which combined a very stable composite material.

Different from regular vinyl floor, there is no plasticizer inside, so it is more environmentally friendly. *Manhattan 69* flooring mainly structured with the UV Coating, a 22mil plus a ceramic bead abrasion resistant paper, decorative paper film and Stone Plastic Composite core board. Meanwhile *W23* underlayment is attached for high end usage.

Product Data:

Thickness	Core	Top layer	Underlayment	Density	Edges	Locking system
0.256" (6.5mm)	0.197" (5mm)	22mil (ceramic bead)	0.60" (1.5mm)	2000kg/m ³	Micro-bevel	UNIPUSH

Dimensions:

Thickness	Length	Width	Sq.ft / box	Planks / box	Boxes / pallet	Pounds / box
0.256" (6.5mm)	60" (1524mm)	9" (229mm)	22.6	6	76	48

Performances:

Fire Behavior	Formaldehyde	Slip Resistance	Sound test
Bf1 S1	E1	DS	IIC 72dB / STC 73dB

100% Waterproof
Earth and Family friendly
Warranty 25 years residential and
10 years light commercial use